

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

Derwent Record

View: [Expand Details](#) Go to: [Delphion Integrated View](#)

[Email this to a friend](#)

Derwent Title: Fly ash based brick prodn. giving dense hard structure - by mixing fly ash, clay and calcium sulphate with water, moulding, drying and sintering for good hardness, etc.

Original Title:  [KR9311260B1](#): METHOD OF FIREBRICK USE WITH FLY ASH

Assignee: PARK B Individual

Inventor: PARK B;

Accession/ 1994-339083 / 199442

Update:

IPC Code: C04B 18/06 ;


Derwent Classes: [L02](#);

Manual Codes: L02-A04(Sintering, firing, hot-pressing, hot extrusion)

Derwent Abstract: (KR9311260B) A fly ash brick is produced by: (1) mixing 70-80 wt.% fly ash having more silicon oxide than aluminium oxide, 15-25 wt.% clay having at least more than 60% kaolin mineral and 5 wt.% gypsum anhydride with 30-45 wt.% water, (2) moulding the mixt. by pressing or extruding (3) drying at 60-70deg.C for 3-5 hours, and (4) sintering 1,050-1,100deg.C for 4-6 hrs.. The used fly ash is pulverised to less than 200 meshes.

Advantage - The obtd. brick has a dense structure, good hardness and good water protection.

Family: PDF Patent Pub. Date Derwent Update Pages Language IPC Code

 [KR9311260B1](#) * 1993-11-29 199442 English C04B 18/06

Local appls.: KR1990000018839 Filed:1990-11-20 (90KR-0018839)

Priority Number:

Application Number	Filed	Original Title
KR1990000018839	1990-11-20	

Title Terms: FLY ASH BASED BRICK PRODUCE DENSE HARD STRUCTURE MIX FLY ASH CLAY CALCIUM SULPHATE WATER MOULD DRY SINTER HARD

[Pricing](#) [Current charges](#)

Derwent Searches: [Boolean](#) | [Accession/Number](#) | [Advanced](#)

Data copyright Thomson Derwent 2003

© 1997-2004 Thomson [Research Subscriptions](#) | [Privacy Policy](#) | [Terms & Conditions](#) | [Site Map](#) | [Contact Us](#) | [Help](#)